



適用機械種類

- 外部受開孔尺寸限制的電控箱
- 改善廠房悶熱局部工作站冷卻應用
- 加工件模具冷卻

APPLICATION

- The external hole size of electrical control panel is limited.
- Cooling for partial workstation
- Cooling for workpiece molding

特性及功能

- 較一般電控箱冷氣風力強。
- 不受特殊電控箱尺寸影響，皆能使用。
- 附萬向輪軸，想吹哪裡都可隨時移動。
- 可調整溫度控制器於一定的溫度範圍內，控制熱源。
- 採用新型高效率環保冷媒，不污染環境。

FEATURE

- The strong wind.
- It's suitable for special dimensions of electrical control panel.
- Attach the caster and can move anywhere.
- Adjust the control board within temperature range and control power source.
- Filling the high-efficiency environmental refrigerant is without pollution.

規格表

CAM SERIES SPECIFICATION

型式 Model		CAM-08S	CAM-12S	CAM-24S
冷卻能力 Cooling capacity	BTU/HR 50/60Hz	6400/8000	9600/12000	19200/24000
	KCAL/HR 50/60Hz	1600/2000	2400/3000	4800/6000
	W 50/60Hz	1860/2325	2790/3488	5580/6976
使用範圍 Operative range	室溫 Room temperature	10°C ~ 40°C		
	箱內溫度 Inside temperature	15°C ~ 30°C		
設定範圍 Setting range	定溫控制 Constant temperature controller	20°C ~ 40°C		
電源 Power Source	V	1ø AC220V 50/60Hz		3ø AC220V 50/60Hz
總負荷電流 Total overburdening current consumption	A	5	6	8
外型尺寸 Dimension (DxWxH)	mm	530x315x986	530x315x986	689x484x1520
冷媒 Refrigerant	gas	R134a/R407C		
總重量 Weight	kg	53	53	125

CAM-□S

- 智慧型溫度控制 Intelligent temperature control
- 冷卻能力 (x1000 BTU/HR) Cooling capacity
- 工廠專用移動式冷氣機 Moving air conditioner for industries

• 特殊規格設計及其他電壓需求請與我司聯絡。
We welcome customized design and other voltage requirement.
• 本公司因技術需求或升級有隨時更改內容、文字、產品規格之權利，更改部分恕不另行通知。
We reserve the right of changing the specifications and modification without any notice.